



ÇALIŞMA ŞARTLARI / OPERATING CONDITIONS	
MAX.TEST BASINCI / MAX.TEST PRESSURE	24 Bar
BASINÇ SINIFI / PRESSURE CLASS (OPTIONAL)	16 Bar
MAX.ÇALIŞMA SICAKLIĞI / MAX. TEMPERATURE	200°C

PARÇA ADI / PART NAME		MALZEME / MATERIAL
1	GÖVDE / BODY	GG25 / GG40.3 / WCB / SS304 / SS316
2	KAPAK / COVER	GG25 / GG40.3 / WCB / SS304 / SS316
3	CAM TESPİT CİVATASI / WINDOW LOCK BOLT	KARBONÇELİK / CARBON STEEL SAE Gr 5 / AISI304
4	TESPİT SAPLAMA SOMUNU / LOCK STUD NUT	KARBONÇELİK / CARBON STEEL SAE Gr 5 / AISI304
5	CAM SIZDIRMAZLIK CONTASI / WINDOW SEALING GASKET	PTFE
6	GÖZETLEME CAMI / SIGHT WINDOW	TERMAL CAM / THERMAL GLASS

FLANŞLI AKIŞ GÖSTERGELERİ PN16 / FLANGED FLUID INDICATORS PN16										
AKIŞ GÖSTERGESİ TİPİ SIGHT FLOW INDICATOR TYPE	ÖLÇÜLER / SIZE									
	L	D	D1	D2	D3	D4	f	b	S	N-Ø
NST-AG1F/DN15	130	95	65	45	41	50	2	14	10	4*14
NST-AG1F/DN20	150	105	75	58	41	50	2	16	10	4*14
NST-AG1F/DN25	160	115	85	68	41	50	2	16	10	4*14
NST-AG1F/DN32	180	140	100	78	71	80	3	16	10	4*18
NST-AG1F/DN40	200	150	110	88	92	98	3	16	10	4*18
NST-AG1F/DN50	230	165	125	102	110	98	3	18	10	4*18
NST-AG1F/DN65	290	185	145	122	135	123	3	18	20	8*18
NST-AG1F/DN80	310	200	160	138	135	123	3	20	20	8*18
NST-AG1F/DN100	350	220	180	158	135	150	3	20	20	8*22
NST-AG1F/DN125	400	250	210	188	185	150	3	22	24	8*26
NST-AG1F/DN150	450	285	240	212	210	150	3	22	26	8*26
NST-AG1F/DN200	600	340	295	268	260	275	3	24	28	12*30

SİPARİŞ ÜZERİNE, DN10 VE ASA NORMUNDA AKIŞ GÖSTERGESİ İMALATI YAPILMAKTADIR.  
UPON REQUEST, FLUID INDICATORS ARE PRODUCED ACC. TO DN10 AND ASA STANDARTS.