


MODEL NST-LT1



BASINÇ SINIFI / PRESSURE CLASS	MAX 16 BAR
FARK BASINCI / DIFFERENTIAL PRESSURE	ΔP 16 BAR
VAKUM / VACUUM	MAX 0,2 BAR MUTLAK BASINÇ / ABSOLUTE PRESSURE

NO:	PARÇA ADI / PART NAME	MALZEME / MATERIAL
1	GÖVDE / BODY	GG25 PİK DÖKÜM / GG25 PIG CASTING GGG40 SFERO DÖKÜM / GGG40 SPHERO CAST AISI304 PASLANMAZ ÇELİK / STAINLESS STEEL SS304 AISI316 PASLANMAZ ÇELİK / STAINLESS STEEL SS316
2	RAKOR / BUSHING	PTFE
3	SİT / SEAT	PTFE
4	MİL / SHAFT	PASLANMAZ ÇELİK / SS416
5	DİSK / DISC	DI & AISI316 & 304 PASLANMAZ ÇELİK / AISI316 & 304 STAINLESS STEEL
6	O-RİNG / O-RING	EPDM,NBR
7	KOL / HANDLE	ALÜMİNYUM / ALUMINIUM
8	SEGMAN / SEGMENT	A3

ÖLÇÜ SIZE	L	H1	H2	H3	L1	D1	D2	D3	C* <sup>c</sup>	4-Ø	G	J	AĞIRLIK / WEIGHT (KGS)		
													KOLSUZ WITHOUT HANDLE	KOLLU WITH HANDLE	DİŞLİ KUTULU GEAR BOX
DN40	33	61		32	198				9*9	4*7	65	50			
DN50	43	88	161	32	198	70	118	125	9*9	4*7	65	50	2.3	4	6.8
DN65	46	89	175	32	198	85	137	145	9*9	4*7	65	50	2.9	4.6	7.4
DN80	46	95	181	32	198	100	143	160	9*9	4*7	65	50	3.7	5.4	8.2
DN100	52	114	200	32	210	122	156	180	11*11	4*7	65	50	5	6.7	9.5
DN125	56	127	213	32	272	148	190	210	14*14	4*10	90	70	6.5	10	11
DN150	56	139	226	32	272	175	212	240	14*14	4*10	90	70	8.1	11.6	12.6
DN200	60	175	260	35	358	226	268	295	17*17	4*12	125	70	18	19.8	27
DN250	68	205	292	35	358	278	325	350	22*22	4*12	125	70	29	30.8	38
DN300	78	235	337	35	358	330	403	400	22*22	4*14	150	102	39	40.8	51
DN350	78	277	368	45	78			460	22*22	4*14	150	125			