



BASINÇ SINIFI / PRESSURE CLASS	MAX 16 BAR
FARK BASINÇ / DIFFERENTIAL PRESSURE	ΔP 16 BAR
VAKUM / VACUUM	MAX 0.2 BAR MUTLAK BASINÇ / ABSOLUTE PRESSURE

NO:	PARÇA ADI / PART NAME	MALZEME / MATERIAL
1	GÖVDE / BODY	RİLSAN KAPLI GG25 PİK DÖKÜM / RILSAN COATED GG25 PIG CASTING RİLSAN KAPLI GGG40 SFERO DÖKÜM / RILSAN COATED GGG40 SPHERO CAST AISI304 PASLANMAZ ÇELİK / STAINLESS STEEL SS304 AISI316 PASLANMAZ ÇELİK / STAINLESS STEEL SS316
2	RAKOR / BUSHING	PTFE
3	SİT / SEAT	HT-EPDM (-35°C~150 °C)
4	MİL / SHAFT	PASLANMAZ ÇELİK / SS416
5	DİSK / DISC	AISI316 & 304 PASLANMAZ ÇELİK / AISI316 & 304 STAINLESS STEEL
6	O-RİNG / O-RING	EPDM,NBR
7	KOL / HANDLE	ALÜMİNYUM / ALUMINIUM
8	SEGMAN / SEGMENT	A3

ÖLÇÜ SIZE	L	4-Ø	H1	H2	H3	L1	C*C	D1	D2	D3	TEPE FLANŞLI TOP PAD SO5211	AĞIRLIK / WEIGHT (KGS)		
												KOLSUZ WITHOUT HANDLE	KOLLU WITH HANDLE	DİŞLİ KUTULU GEAR BOX
DN50	43	8	76	140	32	43	9*9	70	118	120	F05	2.1	2.4	7.3
DN65	46	8	85	152	32	46	9*9	85	137	136,2	F05	2.5	2.8	7.7
DN80	46	8	95	157	32	46	9*9	100	143	160	F05	3.0	3.3	8.2
DN100	52	8	110	176	32	52	11*11	122	156	185	F05	4.8	5.2	6.0
DN125	56	10	125	191	32	56	14*14	148	190	215	F07	6.6	7.0	11.8
DN150	56	10	139	202	32	56	14*14	175	212	238	F07	7.5	7.9	12.7
DN200	60	12	175	243	45	60	17*17	226	268	295	F10	13.8	14.9	26.1
DN250	68	12	203	283	45	68	22*22	278	325	357	F10	21.2	22.3	33.5
DN300	78	12	238	322	45	78	22*22	330	403	407	F10	31.5	42.6	45.9