



BASINÇ SINIFI / PRESSURE CLASS	MAX 16 BAR
FARK BASINCI / DIFFERENTIAL PRESSURE	ΔP 16 BAR
VAKUM / VACUUM	MAX 0.2 BAR MUTLAK BASINÇ / ABSOLUTE PRESSURE

NO:	PARÇA ADI / PART NAME	MALZEME / MATERIAL
1	GÖVDE / BODY	GG25 PİK DÖKÜM / GG25 PIG CASTING GGG40 SFERO DÖKÜM / GGG40 SPHERO CAST AISI304 PASLANMAZ ÇELİK / STAINLESS STEEL SS304 AISI316 PASLANMAZ ÇELİK / STAINLESS STEEL SS316
2	SİT / SEAT	EPDM (-30°C~110 °C) ,NBR,VITON,SILICON
3	DİSK / DISC	DI & AISI316 & 304 PASLANMAZ ÇELİK / AISI316 & 304 STAINLESS STEEL
4	MİL / SHAFT	PASLANMAZ ÇELİK / SS416
5	RAKOR / BUSHING	PTFE
6	O-RİNG / O-RING	EPDM,NBR
7	KOL / HANDLE	ALÜMİNYUM / ALUMINIUM
8	SEGMAN / SEGMENT	A3

ÖLÇÜ SIZE	L	H1	H2	H3	L1	D1	D2	D3	4-Ø	G	J	CXC	AĞIRLIK / WEIGHT (KGS)		
													KOLSUZ WITHOUT HANDLE	KOLLU WITH HANDLE	DIŞLİ KUTULU GEAR BOX
DN25	33			32	198				7	65	50	7*7			
DN32	33			32	198				7	65	50	7*7			
DN40	33			32	198			110	7	65	50	9*9	1.0	1.3	6.2
DN50	43	80	161	32	198	70	118	125	7	65	50	9*9	2.1	2.4	7.3
DN65	46	89	175	32	198	85	137	145	7	65	50	9*9	2.5	2.8	7.7
DN80	46	95	181	32	198	100	143	160	7	65	50	9*9	3.0	3.3	8.2
DN100	52	114	200	32	210	122	156	180	7	65	50	11*11	4.8	5.2	6.0
DN125	56	127	213	32	272	148	190	210	9	90	70	14*14	6.6	7.0	11.8
DN150	56	139	226	32	272	175	212	240	9	90	70	14*14	7.5	7.9	12.7
DN200	60	175	260	35	358	226	268	295	12	125	70	17*17	13.8	14.9	26.1
DN250	68	203	292	35	358	278	325	350	12	125	70	22*22	21.2	22.3	33.5
DN300	78	242	337	35	358	330	403	400	14	125	102	22*22	31.5	42.6	45.9
DN350	78	267	368	45		375	435	460	14	150	125	22*22	38.0	40.0	55.0
DN400	86	309	400	51		439	508	515	14	150	125	27*27	53.0	55.0	87.0
DN450	114	318	422	51		490.5	542	565	22	210	165	27*27	80.0	82.0	112.0
DN500	131	349	479	64		535	592	620	22	210	165	36*36	115.0	117.0	148.0